



Special Features "USF" & "UWF" Type Coupling:

- Specially designed for engine applications.
- Easy to assemble & disassemble.
- Elimination of extension shaft reduces cost of equipment.
- Coupling mounted directly on engine flywheel.

Technical Data

SIZE	RATING HP / 100 RPM	SAE SIZE INCHES	FLANGE DIMENSIONS IN MM				HUB DIMENSIONS IN MM					TOTAL LENGTH MM B
			$\varnothing F$	$\varnothing P$	NO. OF HOLES	HOLES DIA	$\varnothing A$ UWF / USF	$\varnothing E$	D	BORE MIN	BORE MAX	
UWF150 / USF 150	1.72	5.5	190.0	137.0	3	12	111 / 96	80	45	15	48	122
UWF190 / USF 190	2.22	11.5	352.4	333.4	8	10.3	130 / 115	102	54	20	55	107
UWF 225 / USF 225	3.34	11.5	352.4	333.4	8	10.3	142 / 127	108	64	20	60	117
UWF 226	4.51	6.5	216.0	200.0	6	8.5	150 / 141.5	115	70	22	65	136
		8.0	263.5	244.5	6	10.3						
		10.0	314.3	295.3	8	10.3						
		11.5	352.4	333.4	8	10.3						
		14.0	466.7	438.3	8	13.5						
UWF 276	7.39	8.0	263.5	244.5	6	10.3	170 / 161.5	127	80	22	75	148
		11.5	352.4	333.4	8	10.3						
		14.0	466.7	438.2	8	13.5						
UWF 280	11.13	10.0	314.3	295.3	8	10.3	205 / 196.5	140	80	30	80	148
		11.5	352.4	333.4	8	10.3						
		14.0	466.7	438.2	8	13.5						
UWF295	18.21	11.5	352.4	333.4	8	10.3	252 / 243	160	95	40	90	171
		14.0	466.7	438.2	8	13.5						
UWF 2955	30.35	11.5	352.4	333.4	8	10.3	252 / 243	180	108	50	100	184
		14.0	466.7	438.2	8	13.5						